

HSM Pure 220



HSM Pure 220 document shredder

For added data protection at your desk or in the home office. This document shredder with sturdy steel cutting rollers can handle staples and paper clips and even shreds magnetic cards and credit cards in no time at all.

Technical data

Order number:	2320113	Intake width:	8.86"
EAN	4026631053921	Container volume / collecting:	6.6 gal
Cutting type:	strip cut	Collection volume in sheets (80 g):	225
Cutting size:	1/8"	Noise level (idle operation):	ca. 55 - 60 dB(A)
Security level (DIN 66399):	E-2 P-2 T-2	Width x Depth x Height:	14.41" x 10.16" x 18.35"
Cutting capacity in sheets 80g/m²:	12 - 14	Weight:	8.82 lb
Power consumption:	160 W	Shredder material:	Paper, Staples and paper clips, Credit card
Voltage / Frequency:	110-130 V / 60 Hz		


Product information



The hardened steel cutting rollers with a lifetime warranty can easily cope with staples and paper clips and guarantee durability.



To empty the waste container, the housing top can be easily removed – a practical, recessed grip facilitates handling.



The high quality materials and proven HSM "Made in Germany" quality guarantee you are receiving a safe and durable machine.

HSM®



Quiet operation

The quiet operating mode minimises noise development in the workplace which is an important consideration for your staff.



Low power consumption

The stand-by and automatic switch-off features ensure a high degree of energy saving when the shredder is not in use.



Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



High level of user safety

User safety is paramount. A slight pressure on the safety element immediately stops the paper feed and prevents unintentional entry into the machine.



Automatic start/stop

The operation is very easy: the device starts automatically when fed with paper and automatically stops after shredding is complete.



Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).



* Nicht für / not for HSM Pure 320