

# HSM Powerline FA 500.3 - 1/8 x 1 1/2

## HSM Powerline FA 500.3 heavy duty document shredder

The top model of the HSM Powerline heavy duty document shredder range. This powerhouse is perfect for the shredding of large quantities in archives or central document shredding stations.

#### **Technical data**

Order number:	1994117
EAN	4026631055345
Cutting type:	particle cut
Security level (DIN 66399):	E-3 F-1 O-3 P-4 T-4
Cutting capacity in sheets 80g/m²:	180 - 200
Driving power:	10.06 HP
Voltage / Frequency:	208 V / 60 Hz

Intake width:	19.69"
Container volume / collecting:	140 gal
Noise level (idle operation):	ca. 65 dB(A)
Weight:	1995.18 lb
Shredder material:	Paper, Staples and paper clips, Credit card, CD/DVD, USB sticks, Crumpled paper, Floppy disk,

#### **Product information**



We have integrated an automatic oiler into the device which will ensure it runs smoothly, giving you a consistently high cutting capacity and quality.



The device can be used on a mobile basis and has smooth-running, stable castors with a parking brake.



Computer listings

The induction-hardened, solid steel cutting rollers are robust and ensure a high level of durability.





## Specially hardened solid steel cutting rollers

The induction-hardened solid steel cutting rollers are wear-resistant and guarantee durability.



#### **Continuous operation**

Powerful drive allows continuous operation.



#### Compression into boxes or waste bag

The shredded material which has been compressed into compact bales can be cleanly disposed of either in a box (HSM SP 4040 V) or a waste bag (HSM SP 4040 V, HSM SP 5080). These prevent particles from falling out and ensure clean handling.



#### Bale weight can be manually set

The bale weight is variable and depends on your requirement (HSM SP 5080, HSM SP 5088).



### User safety through emergency off switch

It may be necessary to stop the machine immediately so we have equipped the device with an emergency off switch.



#### **Dust extractor**

The powerful and energy efficient dust extractor HSM DE 4-100 in dust classification M ensures an optimal extraction due to the high air flow volume, thereby reducing dust emissions (accessory).







\*HSM Powerline SP 5080 / SP 5088



