HSM Pure 120 - 1/8"



HSM Pure 120 document shredder

Data protection begins at the desk. The compact document shredder shreds personalised advertising, correspondence of all kinds, receipts and payment documents safely and reliably.

Technical data

Order number:	2310113	Intake width:	8.86"
EAN	4026631054034	Container volume /	5.3 gal
Cutting type:	strip cut	collecting:	
Cutting size:	1/8"	Collection volume in sheets (80 g):	180
Security level (DIN 66399):	E-2 P-2 T-2	Noise level (idle operation):	ca. 55 - 60 dB(A)
Cutting capacity in sheets 80g/m²:	10 - 12	Width x Depth x Height:	14.41" x 10.16" x 16.34"
•	4.45.14	Weight:	8.82 lb
Power consumption:	145 W	Shredder material:	Paper, Staples and paper
Voltage / Frequency:	110-130 V / 60 Hz	Sincade material.	clips, Credit card

Product information



The hardened steel cutting rollers with a lifetime warranty can easily cope with staples and paper clips and guarantee durability.



To empty the waste container, the housing top can be easily removed – a practical, recessed grip facilitates handling.



The high quality materials and proven HSM "Made in Germany" quality guarantee you are receiving a safe and durable machine.





Quiet operation

The quiet operating mode minimises noise development in the workplace which is an important consideration for your staff.



Low power consumption

The stand-by and automatic switchoff features ensure a high degree of energy saving when the shredder is not in use.



Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



High level of user safety

User safety is paramount. A slight pressure on the safety element immediately stops the paper feed and prevents unintentional entry into the machine.



Automatic start/stop

The operation is very easy: the device starts automatically when fed with paper and automatically stops after shredding is complete.















Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).







