# HSM Pure 120 - 5/32" x 1"



# **HSM Pure 120 document shredder**

Data protection begins at the desk. The compact document shredder shreds personalised advertising, correspondence of all kinds, receipts and payment documents safely and reliably.

## **Technical data**

Order number:	2313113	Intake width:	8.86"
EAN	4026631054041	Container volume / collecting:	5.3 gal
Cutting type:	particle cut		
Cutting size:	5/32" x 1"	Collection volume in sheets (80 g):	184
Security level (DIN 66399):	E-3 F-1 P-4 T-4	Noise level (idle operation):	ca. 55 - 60 dB(A)
Cutting capacity in sheets 80g/m²:	5 - 6	Width x Depth x Height:	14.41" x 10.16" x 16.34"
	145 W	Weight:	9.92 lb
Power consumption:	145 VV	Shredder material:	Paper, Staples and paper clips, Credit card
Voltage / Frequency:	110-130 V / 60 Hz		

## **Product information**



The hardened steel cutting rollers with a lifetime warranty can easily cope with staples and paper clips and guarantee durability.



To empty the waste container, the housing top can be easily removed – a practical, recessed grip facilitates handling.



The high quality materials and proven HSM "Made in Germany" quality guarantee you are receiving a safe and durable machine.





#### **Quiet operation**

The quiet operating mode minimises noise development in the workplace which is an important consideration for your staff.



#### Low power consumption

The stand-by and automatic switchoff features ensure a high degree of energy saving when the shredder is not in use.



## Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



## High level of user safety

User safety is paramount. A slight pressure on the safety element immediately stops the paper feed and prevents unintentional entry into the machine.



### **Automatic start/stop**

The operation is very easy: the device starts automatically when fed with paper and automatically stops after shredding is complete.















Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).







