



## HSM SECURIO Document Shredders

Product Overview











## HSM SECURIO P-series Department

Data destruction at the highest level. Innovative IntelligentDrive motor and operating technologies – up to 40 % more performance, intelligent prevention of paper jams and a reduced operating noise level.

- Intelligent paper jam prevention. The machine recognises very quickly if too much paper has been fed in and reacts autonomously.
- Powerful motor for continuous operation.
- High degree of user safety with the pressure sensitive safety element.
- Convenient emptying: after opening the door, the reusable collecting bag can be easily removed and emptied.
- Document shredders with particle cut have an integrated automatic oiler for consistently high cutting performance. Reduction in oil quantity by using manual configuration.
- Mobile on castors.



Learn more,  
scan QR-Code.



### Optional

Separate CD cutting unit, cutting size 4 x 7 mm "C"  
Separate OMDD cutting unit, cutting size 2 x 2 mm "M"  
Separate OMDD cutting unit + metal detection "N"

**1** Intuitive operation and menu selection via the high resolution touch display.

**2** IntelligentDrive: Silent, Standard and Performance operating modes for destroying data efficiently and conveniently.

**3** In operating mode Silent up to 30 % quieter than in Standard mode.



Model	HSM SECURIO P36i	HSM SECURIO P40i	HSM SECURIO P44i			
Scope of application	Department, up to 15 persons	Department, up to 15 persons	Department, up to 15 persons			
Cutting type	strip	particle	strip			
Cutting size in mm / Product number	5.8 / 1851121 3.9 / 1850121	4.5 x 30 / 1853121 1.9 x 15 / 1852121 0.78 x 11 / 1855121 1 x 5 / 1854121	5.8 / 1881121 3.9 / 1880121	4.5 x 30 / 1883121 1.9 x 15 / 1882121 0.78 x 11 / 1885121 1 x 5 / 1884121		
Security level ISO/IEC 21964 (DIN 66399) / Shredder material	P-2/O-2/T-2/E-2 P-2/O-2/T-2/E-2 P-2/O-2/T-2/E-2 P-6/T-6/E-5/F-3 P-7/F-3	P-4/O-3/T-4/E-3/F-1 P-5/O-4/T-5/E-4/F-2 P-6/T-6/E-5/F-3 P-7/F-3	P-2/O-2/T-2/E-2 P-5/O-4/T-5/E-4/F-2 P-6/T-6/E-5/F-3 P-7/F-3	P-4/O-3/T-4/E-3/F-1 P-5/O-4/T-5/E-4/F-2 P-6/T-6/E-5/F-3 P-7/F-3		
Cutting capacity in sheets DIN A4 80 g/m <sup>2</sup> (70 g/m <sup>2</sup> )	43-45 (43-49) 34-36 (34-39)	27-29 (27-31) 16-18 (16-20) 11-13 (11-12) 8 (10)	56-58 (56-60) 44-46 (44-47)	34-36 (34-37) 19-21 (19-24) 13-15 (13-15) 9 (11)	77-79 (83-85) 61-63 (67-69)	43-45 (48-50) 25-27 (30-32) 17-19 (20-22) 11 (13)
Noise level in dB(A) in idle operation, standard mode	55	55	55	55	55	55
Intake width in mm	330 / DIN A3	330 / DIN A3	330 / DIN A3	400 / DIN A3	400 / DIN A3	400 / DIN A3
Power consumption in W	1000	1000	1300	1300	1900	1900
Size (W x D x H) in mm	580 x 550 x 1020		580 x 550 x 1020		700 x 592 x 1105	
Weight in kg	64	68	67	72	105	105
Collection volume in l	145	145	145	145	205	205





● **Head office and production sites  
in Germany**

HSM GmbH + Co. KG  
Austraße 1-9  
88699 Frickingen / Germany  
Tel. + 49 7554 2100-0  
Fax + 49 7554 2100-160  
info@hsm.eu  
www.hsm.eu

○ **Subsidiaries**

HSM Técnica de Oficina y  
Medioambiente España, S.L.U.  
HSM France SAS  
HSM (UK) Ltd.  
HSM Polska Sp. z o.o.  
HSM of America LLC

● **Sales and service points**